

Analysis of Methyl Ethyl Sulfide (MES) in Natural Gas using the Agilent 490 Micro GC

Authors

Mohamed Bajja and Remko van Loon, Agilent Technologies, Inc. Middelburg, The Netherlands

Application Note

Micro Gas Chromatography, Natural Gas Analysis, Sulpher Compound Analysis



Introduction

This application note shows the analysis of Methyl Ethyl Sulfide (MES) in natural gas using the Agilent 490 Micro GC. Methyl Ethyl Sulfide is an organosulfur compound with a characteristic odor, and therefore used in some countries as an odorant for natural gas.

This Micro GC column channel is equipped with a special dedicated column, MES in natural gas, for the separation of MES from the other compounds in natural gas. Moreover, this column channel is factory tested to ensure the separation between n-Decane and MES.

If you want to the ability to measure anywhere and get the results you need in seconds, the Agilent 490 Micro GC is the ideal solution. With its rugged, compact, laboratory quality gas analysis platform, the 490 Micro GC generates more data in less time for faster, and better, business decisions.



Instrumentation

Instrument Agilent 490 Micro GC (G3581A)


Column channel MES in natural gas

Column temperature 90 °C

Carrier gas Helium, 70 kPa Injection time 255 msec Injector temperature 110 °C Sampling time 30 sec

Sample information

n-Decane 11 ppm Methyl Ethyl Sulfide (MES) 14 ppm



For More Information

These data represent typical results. For more information on our products and services, visit our Web site at www.agilent.com/chem.

www.agilent.com/chem

Agilent shall not be liable for errors contained herein or for incidental or consequential damages in connection with the furnishing, performance, or use of this material.

Information, descriptions, and specifications in this publication are subject to change without notice.

© Agilent Technologies, Inc., 2011 Printed in the USA August 26, 2011 5990-8750EN

